



CERTIFICATE

No. Z2 053696 2630 Rev. 00

Holder of Certificate:

KOMPAN A/S

C.F. Tietgens Boulevard 32C 5220 Odense SØ DENMARK

Certification Mark:



Product:

Merry-go-round

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.:

713179709-12

Valid until:

131/9/09-12

2025-07-19

Date, 2020-09-01

(Michael Weber)



CERTIFICATE

No. Z2 053696 2630 Rev. 00

Model(s):

GXY801400, GXY801521, GXY801621, GXY916000, GXY916012, GXY916032, GXY944000, GXY944012, GXY957000

Parameters:

GXY801400, GXY801521, GXY801621: Pirouettes: 38 mm steel pipe. Standing area and pipes connected to 100 mm steel foundation with ball bearings.

GXY916000, GXY916012, GXY916032, GXY944000, GXY944012: Track run carousel. A closed PE-Ring is mounted on a steel rail. The rail is anchored in the ground by five pillars. Pillars. Ø: 2.08 m Max. height: 60 cm

The models GXY916000, GXY916012 have a 10° Inclination. GXY957000: Carousel type C with two cantilever beams at the ends two seats with rope connections to the beams.Dimension: Total height above ground 2.62 m Suspension height above ground 2.17 m Height of seat underside above ground 0.71 m Main pole: Ø159 x 4 mm Cantilever top beam: Ø60.3 x 3 mm Cantilever support beam: Ø48.3 x 3 mm

Tested according to:	DIN EN 1176-1:2017 DIN EN 1176-5:2019 EN 1176-1:2017
U	EN 1176-5:2019

Production Facility(ies): 063062